

(19)



(11)

**EP 1 755 706 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
17.03.2010 Bulletin 2010/11

(51) Int Cl.:  
**A61M 5/20** (2006.01) **A61M 5/32** (2006.01)

(21) Application number: **05746205.3**

(86) International application number:  
**PCT/GB2005/002116**

(22) Date of filing: **27.05.2005**

(87) International publication number:  
**WO 2005/115508 (08.12.2005 Gazette 2005/49)**

(54) **INJECTION DEVICE**

INJEKTIONSVORRICHTUNG

DISPOSITIF A INJECTION

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR**

• **BRADY, Matthew**

letchworth  
Hertfordshire SG6 2JE (GB)  
• **HARRISON, Nigel**  
Linton  
Cambridge CB1 6YN (GB)

(30) Priority: **28.05.2004 GB 0412051**

(43) Date of publication of application:  
**28.02.2007 Bulletin 2007/09**

(73) Proprietor: **Cilag GmbH International**  
6300 Zug (CH)

(74) Representative: **Tunstall, Christopher Stephen et al**  
**Carpmaels & Ransford**  
43-45 Bloomsbury Square  
London WC1A 2RA (GB)

(72) Inventors:  
• **HABESHAU, Rosie**  
Cambridge CB1 7TS (GB)  
• **BARROW-WILLIAMS, Tim**  
St Albans, Hertfordshire AL1 1PL (GB)

(56) References cited:  
**WO-A-03/066141 US-A- 3 329 146**  
**US-A- 5 540 660 US-A- 5 957 897**  
**US-A1- 2003 121 815 US-B1- 6 447 480**

**EP 1 755 706 B1**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

## Description

## BACKGROUND TECHNOLOGY

[0001] The present invention relates to an injection device of the type that receives a syringe, extends it, discharges its contents and then retracts it automatically. Devices of this general description are shown in WO 95/35126 and EP-A-0 516 473 and tend to employ a drive spring and some form of release mechanism that releases the syringe from the influence of the drive spring once its contents are supposed to have been discharged, to allow it to be retracted by a return spring.

[0002] Often, such injection devices are required to work with sealed hypodermic syringes which typically have a hermetically sealed cover or "boot" that covers the hypodermic needle and maintains the sterility of the syringe contents. Naturally, it is necessary to maintain the sterility of the syringe contents up to the point of administration, which means that for devices that are designed to be disposable, the boot must be removed with the syringe inside the injection device.

[0003] Typically, the action required to remove the boot from the syringe entails either pulling the boot away from the syringe or twisting the boot and pulling it away from the syringe. If a filled syringe has been around for quite a while before it is used, it is often difficult to remove the boot from the syringe; a substantial force of in excess of 20N is often required.

[0004] If the injection devices are used by patients having rheumatoid arthritis or elderly or weak patients, it is difficult for the patient to remove the boot from the syringe prior to its use. In addition, the boots are small and fiddly to grip for all users but particularly for users who have poor flexibility in their joints or limited manual dexterity. Since the boot of the syringe may be positioned inside the housing, there may also be limited access to the boot.

[0005] US patent no. 5,957,897 discloses a hollow needle applicator for cartridge drugs with a provision for automatic needle retraction after cartridge contents expression. The preamble of claim 1 is based on this document. US patent no. 6,447,480 discloses an injection device where the protective cap has a complementary profile with an intermediate section in the form of a cam.

## SUMMARY OF THE INVENTION

[0006] The injection devices of the present invention are designed to deal with these problems.

[0007] An injection device according to the present invention comprises:

a housing adapted to receive a syringe having a discharge nozzle and a boot that covers its discharge nozzle, the housing defining a first axis and having first and second ends, wherein the discharge nozzle is capable of extending from the first end of the hous-

ing through an exit aperture, the housing further having a camming surface at its first end; and a housing closure member having a camming surface for communicating with the camming surface on the housing so that rotation of the housing closure member about the axis causes the housing closure member to move axially away from the housing; the housing closure member further comprising means for connecting to the boot of the syringe so that removal of the housing closure member from the housing causes removal of the boot from the syringe.

[0008] The camming surfaces on the housing and housing closure means may comprise corresponding curved surfaces.

[0009] The housing closure member may further comprise an external grip feature with which a user can grip the housing closure member.

[0010] One of the housing closure member and the housing may further comprise a ridge with which a corresponding indentation on the other of the housing closure member and the housing can communicate in order to retain the housing closure member on the housing.

[0011] The means for connecting may comprise a pressed grip washer with a profiled internal diameter. In use, the boot would be inserted into the centre of the grip washer, and the profiled internal diameter would deform slightly to surround the boot. In particular, the grip washer may be bent into a frustoconical shape. However, as the cap is removed, the grip washer would dig into the boot and prevent it from being removed from the cap.

[0012] The internal diameter of the grip washer may be castellated. Alternatively, the grip washer may comprise an internally toothed star washer or shakeproof washer.

[0013] The means for connecting may be formed from metal.

[0014] The means for connecting may be held in an indentation moulded into the housing closure means.

[0015] The means for connecting may be housed in a central boss moulded into the inside of the housing closure means. The means for connecting may be held in place in the housing closure means by an indentation moulded in to the central boss.

[0016] Alternatively, the means for connecting may be moulded from the same material as the housing closure means, as part of a central boss moulded into the inside of the housing closure means.

[0017] The means for connecting may comprise a central boss having a hollow end, wherein a lip of the hollow end is bevelled on its leading edge but not on its trailing edge. In use, the boot would ride over the bevelled edge as it was inserted into the housing closure means. However, as the housing closure means is removed, the trailing edge would dig into the boot and prevent it from being removed from the housing closure means.

[0018] The housing closure means may further com-

prise a support surface for supporting an end of a boot of a syringe.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0019] The invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 shows a perspective view of an injection device according to the present invention with the housing closure member removed and the needle in an extended position;

Figure 2 shows a plan view of the injection device of figure 1;

Figure 3 shows a side view of the injection device of figure 1;

Figure 4 shows a perspective view of the injection device of figures 1 to 3, with the housing closure member in place;

Figure 5 shows a plan view of the injection device of figure 4;

Figure 6 shows a perspective view of a castellated grip washer for use in an injection device according to an embodiment of the present invention;

Figure 7 shows a housing closure member for use in an injection device according to an embodiment of the present invention;

Figure 8 shows the cap of figure 7 when engaged with a syringe boot of a syringe used with an injection device according to an embodiment of the present invention; and

Figure 9 shows a cross-sectional view of part of an injection device according to an embodiment of the present invention.

#### DETAILED DESCRIPTION

[0020] Figures 1 to 5 and 9 show an injection device 110 according to a first embodiment of the present invention. The injection device has an injection device housing 112.

[0021] The housing 112 contains a hypodermic syringe 114 of conventional type, including a syringe body 116 defining a reservoir and terminating at one end in a hypodermic needle 118. The syringe 114 has a hermetically sealed cover or "boot" that covers the hypodermic needle 118 and maintains the sterility of the syringe contents. The boot is generally formed of a soft rubber or plastics material. Whilst the syringe illustrated is of hy-

podermic type, this need not necessarily be so. Transcutaneous or ballistic dermal and subcutaneous syringes may also be used with the injection device of the present invention.

5 [0022] The injection device is further provided with a cap 130. As is best seen from figures 1 to 3 and 7, the cap is retained on the housing 112 by a ridge 113 on the housing 112, and a corresponding indentation 131 on the inside of the cap 130.

10 [0023] Close to the end of the housing 112 from which the hypodermic needle can extend, there is provided a curved camming surface 150 which corresponds with another curved camming surface 152 on the cap 130.

[0024] As can be seen from figures 7 and 8, the interior of the cap 130 is provided with a castellated grip washer 160. This grip washer 160 is shown in figure 6. The grip washer 160 is held in place in the cap 130 by a corresponding indentation 162 which is moulded into the interior of the cap 130.

20 [0025] The exterior of the cap 130 is provided with a pair of grip surfaces 170. These grip surfaces 170 provide a surface through which the user can grip the cap 130.

[0026] As can be seen from figure 9, the interior of the cap 130 may be provided with a support surface 180 which supports the end of the boot 120.

25 [0027] During manufacture of the injection device 110, the syringe 114 and boot 120 are inserted into the housing as a single piece. The cap is placed onto the housing such that the boot 120 is forced into the centre of the castellated washer 160 and the ridge 113 on the housing engages with the indentation 131 in the cap 130. In addition the two camming surfaces 150, are aligned. By forcing the boot 120 into the castellated washer 160, the castellations deform so that the washer takes up a slightly frustoconical shape. The metal from which the washer 160 is formed cuts into the softer plastics or rubber material from which the boot 120 is formed. Consequently a very firm grip is produced on the boot 120.

35 [0028] When the injection device 110 is to be used, the user holds the housing with one hand, and grips the cap 130 with the other hand using the grip surfaces 170. The user then rotates the cap 130. In rotating the cap 130, the two camming surfaces 150, 152 move over each other, and the cap 130 is moved axially away from the housing 112. This rotational and axial movement also twists and pulls the boot 120 off the syringe 114. The boot 120 is held stationary within the cap 130 by the castellated washer 160 because the force required to twist the boot 120 and remove it from the syringe 114 is significantly less than that required to pull the boot 120 out of the centre of the castellated washer 160. The support surface 180 helps to prevent the boot 120 from being pulled away from the syringe 114 at an angle, by maintaining the axial alignment of the boot 120 within the cap 130.

55 [0029] The present invention provides a simple and effective way of solving the problems of the prior art devices. Since no modifications need to be made to the

syringe or boot, a standard syringe can be used, and manufacturing costs can be reduced. Furthermore, the tolerances with which the syringe and boot are positioned within the housing are not critical since once the boot has been inserted into the castellated washer, it cannot be removed. It does not matter how much of the boot extends through the washer, provided that the washer grips the boot sufficiently. Since the insertion depth and exact size of the syringe and boot can be subject to variation, this is a significant advantage.

[0030] In addition, the number of operational steps required to use the device is minimised since it is not necessary to perform two separate steps to remove the cap and the boot.

## Claims

### 1. An injection device (110) comprising:

a housing (112) adapted to receive a syringe (114) having a discharge nozzle (118) and a boot (120) that covers its discharge nozzle, the housing defining a first axis and having first and second ends, wherein the discharge nozzle is capable of extending from the first end of the housing through an exit aperture, the housing further having a camming surface (150) at its first end; and characterised by:

a housing closure member (130) having a camming surface (152) for communicating with the camming surface on the housing so that rotation of the housing closure member about the axis causes the housing closure member to move axially away from the housing, wherein the housing closure member further comprises means (160) for connecting to the boot of the syringe so that removal of the housing closure member from the housing causes removal of the boot from the syringe.

### 2. An injection device according to claim 1 wherein the camming surfaces on the housing and housing closure means comprise corresponding curved surfaces.

### 3. An injection device according to claim 1 or claim 2 further comprising an external grip feature (170) with which a user can grip the housing closure member.

### 4. An injection device according to any preceding claim, wherein one of the housing closure member and the housing further comprise a ridge (113) with which a corresponding indentation (131) on the other of the housing closure member and the housing can communicate in order to retain the housing closure mem-

ber on the housing.

### 5. An injection device according to any preceding claim wherein the means for connecting comprises a pressed grip washer (160) with a profiled internal diameter.

### 6. An injection device according to claim 5 wherein the internal diameter of the grip washer is castellated.

### 7. An injection device according to claim 5, wherein the grip washer comprises an internally toothed star washer or shakeproof washer.

### 8. An injection device according to any of claims 5 to 7, wherein, upon connecting the boot of the syringe to the housing closure member, the grip washer is bent into a frustoconical shape.

### 9. An injection device according to any preceding claim, wherein the means for connecting is formed from metal.

### 10. An injection device according to any preceding claim wherein the means for connecting is held in an indentation moulded into the housing closure means.

### 11. An injection device according to any preceding claim wherein the means for connecting is housed in a central boss moulded into the inside of the housing closure means.

### 12. An injection device according to claim 11, in which the means for connecting is held in place in the housing closure means by an indentation (162) moulded into the central boss.

### 13. An injection device according to any of claim 1 to 4, wherein the means for connecting is moulded from the same material as the housing closure means, as part of a central boss moulded into the inside of the housing closure means.

### 14. An injection device according to claim 13, wherein the means for connecting comprises a central boss having a hollow end, wherein a lip of the hollow end is bevelled on its leading edge but not on its trailing edge.

### 15. An injection device according to any preceding claim, further comprising a support surface (180) for supporting an end of a boot for a syringe.

## Patentsprüche

### 1. Eine Injektionsvorrichtung (110), aufweisend:

ein Gehäuse (112) welches ausgestaltet ist, eine Spritze (114) aufzunehmen mit einer Auslassdüse (118) und einer Schutzmanschette (120), welche deren Auslassdüse umgibt, wobei das Gehäuse eine erste Achse definiert und erste und zweite Enden aufweist, wobei die Auslassdüse in der Lage ist, sich von dem ersten Ende des Gehäuses durch eine Ausgangsöffnung hindurch zu erstrecken, wobei das Gehäuse weiterhin aufweist eine Anlagefläche (150) an seinem ersten Ende; und **gekennzeichnet durch:**

- ein Gehäuseverschlussmittel (130) mit einer Anlageoberfläche (152) zum Kommunizieren mit der Anlageoberfläche auf dem Gehäuse, so dass eine Rotation des Gehäuseverschlussmittels um die Achse bewirkt, dass sich das Gehäuseverschlussmittel axial wegbewegt von dem Gehäuse, wobei das Gehäuseverschlussmittel weiterhin Gehäuseverschlussmittel (160) zur Herstellung einer Verbindung mit der Schutzmanschette der Spritze aufweist, so dass das Entfernen des Gehäuseverschlussmittels von dem Gehäuse ein Entfernen der Schutzmanschette von der Spritze bewirkt.
2. Eine Injektionsvorrichtung gemäß Anspruch 1, wobei die Anlageoberflächen auf dem Gehäuse und das Gehäuseverschlussmittel korrespondierende gekrümmte Oberflächen aufweisen.
3. Eine Injektionsvorrichtung gemäß Anspruch 1 oder Anspruch 2, weiterhin aufweisend eine externe Greifvorrichtung (170), mit welcher eine Bedienperson das Gehäuseverschlussmittel greifen kann.
4. Eine Injektionsvorrichtung gemäß einem der vorhergehenden Ansprüche, wobei entweder das Gehäuseverschlussmittel oder das Gehäuse weiterhin aufweist eine Erhöhung (113), mit welcher eine korrespondierende Einkerbung (131) auf jeweils dem Gehäuseverschlussmittel oder dem Gehäuse kommunizieren kann, um das Gehäuseverschlussmittel auf dem Gehäuse zu halten.
5. Eine Injektionsvorrichtung gemäß einem der vorhergehenden Ansprüche, wobei das Mittel zum Verbinden eine gepresste Greifscheibe (160) mit einem profilierten inneren Durchmesser aufweist.
6. Eine Injektionsvorrichtung gemäß Anspruch 5, wobei der innere Durchmesser der Greifscheibe zinnenartig ausgebildet ist.
7. Eine Injektionsvorrichtung gemäß Anspruch 5, wobei

bei der Greifscheibe eine innere gezahnte Sternscheibe oder eine rüttelfeste Scheibe aufweist.

8. Eine Injektionsvorrichtung gemäß einem der Ansprüche 5 bis 7, wobei beim Verbinden der Schutzmanschette der Spritze mit dem Gehäuseverschlussmittel die Greifscheibe in eine kegelförmige Form gebogen wird.
9. Eine Injektionsvorrichtung gemäß einem der vorhergehenden Ansprüche, wobei das Mittel zum Verbinden aus Metall gebildet ist.
10. Eine Injektionsvorrichtung gemäß einem der vorhergehenden Ansprüche, wobei das Mittel zum Verbinden in einer Einkerbung gehalten wird, welche in das Gehäuseverschlussmittel eingeformt ist.
11. Eine Injektionsvorrichtung gemäß einem der vorhergehenden Ansprüche, wobei das Mittel zum Verbinden gelagert ist in einem zentralen Wulst, welcher eingeformt ist in die Innenseite des Gehäuseverschlussmittels.
12. Eine Injektionsvorrichtung gemäß Anspruch 11, wobei das Mittel zum Verbinden an Ort und Stelle in dem Gehäuseverschlussmittel gehalten wird durch eine Einkerbung (162), welche in den zentralen Wulst eingeformt ist.
13. Eine Injektionsvorrichtung gemäß einem der Ansprüche 1 bis 4, wobei das Mittel zum Verbinden aus demselben Material geformt wird wie das Gehäuseverschlussmittel, als Teil eines zentralen Wulstes, welcher in die Innenseite des Gehäuseverschlussmittels eingeformt ist.
14. Eine Injektionsvorrichtung gemäß Anspruch 13, wobei das Mittel zum Verbinden einen zentralen Wulst aufweist, welcher ein hohles Ende aufweist, wobei eine Lippe des hohlen Endes abgeschrägt ist auf ihrer Führungskante aber nicht auf ihrer Hinterkante.
15. Eine Injektionsvorrichtung gemäß einem der vorhergehenden Ansprüche, weiterhin aufweisend eine Unterstützungsoberfläche (180) zum Unterstützen eines Endes einer Schutzmanschette für eine Spritze.

## Revendications

1. Dispositif d'injection (110) comprenant :

un logement (112) adapté pour recevoir une seringue (114) ayant une buse de décharge (118) et une tétine (120) qui recouvre sa base de dé-

charge, le logement définissant un premier axe et ayant des première et deuxième extrémités, dans lequel la buse de décharge est capable de s'étendre à partir de la première extrémité du logement par l'intermédiaire d'une ouverture de sortie, le logement ayant en outre une surface de verrouillage (150) à sa première extrémité ; et




caractérisé par :

un élément de fermeture de logement (130) ayant une surface de verrouillage (152) pour communiquer avec la surface de verrouillage sur le logement de façon que la rotation de l'élément de fermeture de logement autour de l'axe provoque le déplacement de l'élément de fermeture de logement axialement en s'éloignant du logement, dans lequel l'élément de fermeture de logement comprend en outre des moyens (160) pour se connecter à la tétine de la seringue de façon que le retrait de l'élément de fermeture de logement à partir du logement provoque le retrait de la tétine à partir de la seringue.

2. Dispositif d'injection selon la revendication 1, dans lequel les surfaces de verrouillage sur le logement et les moyens de fermeture de logement comprennent des surfaces incurvées correspondantes.
3. Dispositif d'injection selon la revendication 1 ou la revendication 2, comprenant en outre une fonction de poignée externe (170) avec laquelle un utilisateur peut saisir l'élément de fermeture de logement.
4. Dispositif d'injection selon l'une quelconque des revendications précédentes, dans lequel l'un parmi l'élément de fermeture de logement et le logement comprend en outre une saillie (113) avec laquelle une échancrure correspondante (131) sur l'autre parmi l'élément de fermeture de logement et le logement peut communiquer afin de maintenir l'élément de fermeture de logement sur le logement.
5. Dispositif d'injection selon l'une quelconque des revendications précédentes, dans lequel les moyens de connexion comprennent une rondelle de poignée comprimée (160) ayant un diamètre interne profilé.
6. Dispositif d'injection selon la revendication 5, dans lequel le diamètre interne de la rondelle de poignée est cranté.
7. Dispositif d'injection selon la revendication 5, dans lequel la rondelle de poignée comprend une rondelle en étoile dentée à l'intérieur ou une rondelle indesserrable.
8. Dispositif d'injection selon l'une quelconque des re-

vendications 5 à 7, dans lequel, lors de la connexion de la tétine de la seringue à l'élément de fermeture de logement, la rondelle de poignée est incurvée en une forme tronconique.

9. Dispositif d'injection selon l'une quelconque des revendications précédentes, dans lequel les moyens de connexion sont formés de métal.
10. Dispositif d'injection selon l'une quelconque des revendications précédentes, dans lequel les moyens de connexion sont maintenus dans une échancrure moulée à l'intérieur des moyens de fermeture de logement.
11. Dispositif d'injection selon l'une quelconque des revendications précédentes, dans lequel les moyens de connexion sont logés dans un bossage central moulé à l'intérieur des moyens de fermeture de logement.
12. Dispositif d'injection selon la revendication 11, dans lequel les moyens de connexion sont maintenus en place dans les moyens de fermeture de logement par une échancrure (162) moulée à l'intérieur du bossage central.
13. Dispositif d'injection selon l'une quelconque des revendications 1 à 4, dans lequel les moyens de connexion sont moulés en le même matériau que les moyens de fermeture de logement, sous la forme d'une partie d'un bossage central moulé à l'intérieur des moyens de fermeture de logement.
14. Dispositif d'injection selon la revendication 13, dans lequel les moyens de connexion comprennent un bossage central ayant une extrémité creuse, dans laquelle une levée de l'extrémité creuse est biseautée sur son bord d'attaque mais pas sur son bord de fuite.
15. Dispositif d'injection selon l'une quelconque des revendications précédentes, comprenant en outre une surface de support (180) pour supporter une extrémité d'une tétine pour une seringue.









FIG. 6




FIG. 7




FIG. 8





FIG. 9



**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- WO 9535126 A [0001]
- EP 0516473 A [0001]
- US 5957897 A [0005]
- US 6447480 B [0005]